

Temperature ranges
-80°C + 80°C







DESCRIPTION

TOP PLUS multi-purpose extinguishing dry powder capable to fight A,B, and C fires, certified according to EN615. Our TOP PLUS powder is with new superior additives and different granulometry, thus ensuring top performances. We manufacture the extinguishing powder within our plants: the entire production cycle is 100% under our control. We respect the most stringent quality standards, sometimes stricter than the regulation


TECHNICAL DATA

FIRE CLASSES		ABC		
EXTINGUISHING AGENT		Monoammonium phosphate		
	Monoammonium phosphate	24% ± 1,5%		
CHEMICAL COMPOSITION	Ammonium sulfate	67% ± 3%		
	Additives	<10% ± 1%		
APPARENT VOLUMETRIC MASS (EN615)		0,84 g/ml ± 0,07 g/ml		
	125 μm	6% ± 5%		
GRANULOMETRY (EN615)	63 μm	22% ± 8%		
	40 μm	41% ± 8%		
	Method	Alpine Airjet Sieve		
CONGLOMERATION RESISTANCE		No sieve residue at 425 μm		
HYDROPHOBIA		No complete absorption of water droplets		
WATER CONTENT		<0,2		
TEMPERATURE RANGES		-80°C + 80°C		
CONFORMITY		EN615 compliant		

PACKAGING

All our extinguishing powder bags are packed in our Italian factories, ready to be delivered all over the world. There are other packaging available on request with minimum order quantity







BAG 12,5 KG ABC POWDER



BAG 25 KG ABC POWDER



BIG BAG 1000 KG ABC POWDER

RANGE

Our wide range of extinguishing powder types:

Packaging	A32	A33	A35	A42	A52	A72	A92	TOP
3 Kg	✓	✓	✓	✓	✓	✓	✓	✓
12,5 Kg	✓	✓	✓	✓	✓	✓	\checkmark	✓
25 Kg	✓	✓	✓	\checkmark	✓	✓	\checkmark	✓
1.000 Kg	✓	✓	✓	✓	✓	✓	✓	✓

www.anaf.eu info@anaf.eu